



RD Type

#### NOTES:

1. TYPE: HIGH PRESSURE HYDRAULIC CYLINDER CONFORMED TO N.F.P.A. SPECIFICATIONS AND ANSI B93.15-1981.
2. OPERATING PRESSURE: 3000 PSI (RESTRICTIONS ON SOME MOUNTINGS).
3. OPERATING TEMPERATURE: -30°C TO 80°C (-30°F TO 180°F). UP TO 250°C (450°F) FOR VITON SEALS. LOW TEMPERATURE SEALS ALSO AVAILABLE.
4. STANDARD BORE SIZE: 9 BORE SIZES FROM 1 1/2" TO 8". LARGER BORE SIZES TO 14". CONSULT FACTORY FOR DIMENSIONS.



1100, rue Michèle-Bohec  
Blainville (Québec)  
J7C 5N5 Canada  
Ph: 450-434-0216

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. RDC Control makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**HP-3000-BC-100**

HEAVY DUTY HYDRAULIC CYLINDERS  
(BASIC CYLINDER)

SCALE	NTS
UNIT	INCH
SHEET	1 of 1